



## Piloted Drill

Date: \_\_\_\_\_ PO #: \_\_\_\_\_  
 Distributor: \_\_\_\_\_ Location: \_\_\_\_\_  
 Contact: \_\_\_\_\_ Phone: \_\_\_\_\_  
 Email: \_\_\_\_\_ Fax: \_\_\_\_\_  
 # of Pieces: \_\_\_\_\_ Hardness: \_\_\_\_\_  
 Material: \_\_\_\_\_




\*\* CHECK HERE TO SELECT SPECIAL SHANK, THEN SELECT SHANK DESIGNATION BELOW \*\*



Threaded UNF-2A  
 1/4-28  
 5/16-24  
 3/8-24




Zephyr  
 1/4-28  
 10-32



Quick Change



Tri - Flat



Reduced Shank

Tool Specifications: Modify Standard Tool  Yes  No EDP# \_\_\_\_\_

Point Angle:  118°  135° Special Angle: \_\_\_\_\_

Coating: \_\_\_\_\_ L1: \_\_\_\_\_ L2: \_\_\_\_\_

D1: \_\_\_\_\_ D2: \_\_\_\_\_ D3: \_\_\_\_\_ OAL: \_\_\_\_\_

Special Instructions: \_\_\_\_\_

\_\_\_\_\_

Standard tolerances used unless otherwise specified  
 .x = ± .1  
 .xx = ± .01  
 .xxx = ± .005  
 .xxxx = ± .0005  
 Fractions = ± 1/64"  
 Angular = ± 3°